

ORDNANCE TRAINING SOLUTIONS ®

FlashBang Grenade Simulator FLASHBANG GEN 2 ™

- Inert
- TSC Sensitive. WIDS compliant; no WiFi, Bluetooth or cell phone capability
- Fits most load-out pouches
- 103dB audible feedback
- LED strobe visual feedback
- Field-replaceable A23 style battery yields 100+ throws without reloading
- FindMe™ alarm



FlashBang Gen 2 [™] Flash-Grenade incorporates the latest technological advancements making this new generation distraction device the preferred choice meeting stringent training requirements of today's military, law enforcement and security professionals.

FlashBang Gen 2 is Inert, provides consistent (MCU controlled) fuse and run times, offers multiple throws per training session, and reloads

easily in the field with readilyavailable A23 style battery.

Specifically designed to withstand rigorous environments utilizing extremely durable urethane materials, provides reliable and repeatable operations for indoor, outdoor, day and night training exercises to practice critical timing. repetitive memory and procedural skills where an actual grenade would ordinarily be used.

Technical Surveillance Counter Measures considered, this device does not receive or transmit electronic data via WiFi, Bluetooth or cell phone.

Visual and audible feedback provides non-kinetic grenade simulation via high-intensity LED strobe and powerful siren, powered by off-the-shelf, field-replaceable, A23 style battery.

Simple operation: remove pull ring, and throw. Following a 1.5 second fuse delay, the integral siren and LED strobe will alarm for 4 seconds. Retrieve, replace the pull ring, and the device is ready for another exercise.

Specifications *

Controls

1.25" Pull Ring Activates / Secures for exercises, storage and transport.

Spoon Spring-actuated microswitch starts / stops micro-controlled timer (fuse simulator) operations.

Mode of Operation Releasing the Spoon activates integral MCU. After a 1.5 second initial pause, the

internal siren and LED strobe activates 4 seconds. FindMe™ mode provides visual and audible alerts @ 7min intervals until spoon is secured.

ELECTRICAL

Power Required Qty 1, A23 style Miniature Alkaline Battery; nominally 12V 55mAh. Field-replaceable.

Integral PCBA Micro-controlled precise timing, over-current and reverse-polarity protection, and battery holder.

Integral Siren Typically 103 ±5 dB(A) at 15 Vdc at 24 inches (61 cm) at 25°C.

Integral LED Strobe

MECHANICAL

Material Molded Urethane Rubber

TBDgm, TBDlb Weight

Dimensions 38.1mm (1.5in) Dia X 149.25mm (5.9in) High

Color Translucent Yellow body with white spoon. Call for custom colors.

Warranty 1yr

ORDERING INFORMATION FRAGBANG GEN 2[™] M84SIMG2

ACCECESSORIES

Spoon Kit Screw Kit Carry Case Battery

mastercard

Pull Ring Kit M67SIMG2 PRing M84SIMG2 Spoon M84SIMG2 Screws M84SIMG2 Case A23 Battery

Ordnance Training Solutions ® 10334 Cogdill Rd Knoxville TN 37932 USA Phone (865) 777-0099 www.ordnancetrainingsolutions.com

Visit us on YouTube for instructional videos Custom designs available on request *Specifications subject to change without notice.

FLASHBANGG2_DS Rev 0





