

ORDNANCE TRAINING SOLUTIONS ®

M67 Fragmentation Grenade Simulator

FRAGBANG GEN 2 ™

- Inert
- **TSC Sensitive. WIDS** compliant; no WiFi, Bluetooth or cell phone capability
- Fits most load-out pouches
- 103dB audible feedback
- LED strobe visual feedback
- **Battery-powered field**replaceable A23 style battery yields 100+ throws without reloading
- FindMe™ alarm



FragBang Gen 2 ™ is a costeffective, and multi-operational training aid for today's military, law enforcement and security professionals to practice critical timing, repetitive memory and procedural skills in training sessions where an actual grenade would ordinarily be used.

This training aid is specifically designed to withstand rigorous

environments utilizing extremely durable urethane materials to provide reliable and repeatable operations for indoor, outdoor, day and night training exercises.

Technical Surveillance Counter Measures were also considered. This device does not receive or transmit electronic data via WiFi. Bluetooth or cell phone.

Visual and audible feedback provides non-kinetic grenade simulation via high-intensity LED strobe and powerful siren, powered by off-the-shelf, field-replaceable, A23 style battery.

Operation is straightforward; hold the grenade, remove pull ring, and throw. 4 seconds later the siren will pulse and LED strobe will flash for 4 seconds. Retrieve the grenade. replace the pull ring, and the grenade is ready for another exercise.

Specifications *

Controls

1.25" Pull Ring Activates / Secures for exercises, storage and transport.

Spoon Spring-actuated microswitch starts / stops micro-controlled timer (fuse simulator) operations.

Mode of Operation Releasing the Spoon activates integral microcontroller. After a 4 second initial pause, the internal siren and LED strobe activates for 4 seconds, then pauses for Spoon to be replaced, ready for another exercise.

If Spoon is not replaced, microcontroller initiates FindMe ™ mode. executing audible and visual alerts

@ 7 minute intervals to facilitate locating the device.

ELECTRICAL

Power Required Qty 1, A23 style Miniature Alkaline Battery; nominally 12V 55mAh. Field-replaceable.

Integral PCBA Micro-controlled precise timing, over-current and reverse-polarity protection, and battery holder.

Integral Siren Typically 103 ±5 dB(A) at 15 Vdc at 24 inches (61 cm) at 25°C.

Integral LED Strobe

MECHANICAL

Weight 148gm, 0.326lb

Dimensions 71mm (2.8in) Dia X 106mm (4.2in) High

Color Translucent Red body with white spoon. Call for custom colors.

Warranty 1yr

ORDERING INFORMATION FRAGBANG GEN 2[™] M67SIMG2

ACCECESSORIES

Spoon Kit Screw Kit Carry Case Battery

Pull Ring Kit M67SIMG2 PRing M67SIMG2 Spoon M67SIMG2 Screws M67SIMG2 Case A23 Battery

Ordnance Training Solutions® 10334 Cogdill Rd Knoxville TN 37932 USA Phone (865) 777-0099 Fax (865) 777-0094

Visit us on YouTube for instructional videos Custom designs available on request *Specifications subject to change without notice.

M67SIMG2_DS Rev 2





Order with confidence



